

Gen-Eye GL™

Pipe Inspection/Location System



With DVD Recorder and Self-Leveling Camera

The Gen-Eye GL offers a DVD recorder to provide a crisp picture with a jitter free freeze frame, allowing you to better analyze any problem. The separate 10.6" LCD color monitor provides you with a sharp picture. It's recessed for better visibility on bright days.



The self-leveling color camera automatically keeps your picture right side up as the camera glides through the line. No more tilting your head to adjust for the twisting of the camera or explaining to a customer why the water is on the top of the screen. You always have an upright picture on the monitor, making it easier for you and your customers to follow the action.

Backed by a two-year warranty, the Gen-Eye GL system includes everything you need to troubleshoot 2" through 10" lines, including:

Titler with full keyboard

The on-screen titler keyboard is virtually indestructible. It's impervious to water, dirty hands and grime from the field. You get up to nine pages of text to add your company name and job location to each video you make.

Built-in AC/DC converter

Allows you to operate in the field with truck power alone.

Built-in voice over unit

Internal microphone and on/off switch lets you add commentary to your videos.

On-screen distance counter

Lets you keep track of how much push-rod you've fed into the line.

Date and Time Stamp

You can document the date and time of each job for your records.

Other features include

Internal 512 Hz transmitter, picture inverter, dimmer control, panel mount fuses, and trap skid.

Need a more compact system?

The Mini-Monitor package fits in a smaller space and a smaller budget. And it has some of the features of the full size Command Module.



General
PIPE CLEANERS
www.drainbrain.com

Gen-Eye GL™

Big capacity reels

The full size reel holds 200 ft., 300 ft., or 400 ft. of push-rod on a sturdy frame and takes up little space in your truck.

Eight inch wheels ensure easy transport to and from the job. The mini reel carries 100 ft. or 200 ft. of push-rod in a compact frame for easy handling without taking up too much room in your truck.

Flexibility, Strength, Durability

A tough, Gel-Rod® push-rod protects against moisture damage if the rod is cut or abraded. Its Kevlar® braid, fiberglass core, and durable sheath provide for maximum pushing and pulling power.

Sturdy case with wheels

All the electronics are protected in a sturdy case with wheels, telescoping handle, and a tilt stand for convenient viewing, transport and maneuverability.



Skid designs

Skids keep the camera centered in the pipe for a better view, while reducing drag on longer runs. Full size systems include both 3" and 6" trap skids that protect the camera from abrasion as it slides through cast iron traps. Optional 3-in-1 skid set for 4", 6" and 8" lines, and Universal Roller Skid for 6" to 12" lines are also available.



Gen-Eye GL Units

- GL-500** Gen-Eye GL Command Module, complete with DVD Recorder, 10.6" LCD Screen, and Full Keyboard.
- SL-GL-A** Gen-Eye GL Command Module with 200 ft. of Push-Rod, Full Size Reel, Self-Leveling Color Camera, and 3" & 6" Trap Skids.
- SL-GL-B** Same as SL-GL-A, plus Digital Locator with Padded Bag.
- C-M-GL-A** Gen-Eye GL Command Module with 100 ft. of Mini Rod, Mini-Reel, Mini Color Camera, and 3" Trap Skid.
- C-M-GL-B** Same as C-M-GL-A, plus Digital Locator with Padded Bag.

Other Models Available



Gen-Eye GL Specifications:

	Self-Leveling Color Camera	Standard Color Camera	Mini Color Camera
Line Capacity	3" to 10"	3" to 10"	2" to 4"
Reel Capacity	200, 300, 400 ft.	200, 300, 400 ft.	100 or 200 ft.
Sensitivity	.5 Lux	.5 Lux	.5 Lux
Lighting	16 White LED's	16 White LED's	8 White LED's
White Balance	Auto High Speed	Auto High Speed	Auto High Speed
Camera Dimensions	1.375" Dia. x 2.3" Long	1.375" Dia x 1.85" Long	1" Dia. x 1.8" Long
Push-Rod Diameter	.475" Gel-Rod®	.475" Gel-Rod®	.400" Gel-Rod®
Reel Dimensions	29" L x 16" W x 33-1/2" H	29" L x 16" W x 33-1/2" H	18" L x 16" W x 19" H
Gen-Eye GL Case Dimensions	20" L x 16" W x 19" H	20" L x 16" W x 19" H	20" L x 16" W x 19" H
Video Format	NTSC or PAL	NTSC or PAL	NTSC or PAL
Power	110v/60 Hz AC, 12 VDC	110v/60 Hz AC, 12 VDC	110v/60 Hz AC, 12 VDC
Operating Temperature	14° F to 122° F -10° C to 50° C	14° F to 122° F -10° C to 50° C	14° F to 122° F -10° C to 50° C

General / **General Wire Spring Co.**
PIPE CLEANERS
 1101 Thompson Avenue • McKees Rocks, PA 15136 USA
 800-245-6200 or 412-771-6300 • Fax: 412-771-2771
 www.drainbrain.com • e-mail: info@drainbrain.com

The toughest tools down the line.™