

Accessories



Snake Oil™

Protects your cables better than common lubricants. Its special rust inhibitor cuts through moisture and replaces it with a rust-resistant coating. In addition, Snake-Oil gives your equipment a fresh, clean smell.



Catalog Number

Description

SOQ	1 Quart Snake-Oil
SOQ-12	12 Quarts Snake-Oil
SOG	1 Gallon Snake-Oil
SOG-4	4 Gallons Snake-Oil




MGT Manhole Guide Tube

Supports drain cables in manholes. Adjusts from 6'2" to 9'4". 4'4" extensions available.



SG Cable Starter Guide

Guides cable away from trap. Position in pipe by hooking wire into hole in Guide.



SIG Splash/Impact Goggles

Can be worn over glasses.



QF "Quick Fix" Repair Coupler

Just screw on tightly and it won't come off. For 1/2", 5/8", and 3/4" sizes.



FC Butt-Weld Connector

Passes through automatic feeds. No need to adjust feed. For 5/8", and 3/4" sizes.



FC-O Cup Type Connector

Sheath fits over cable for easier repairs. For 5/16", 3/8", 1/2", 5/8" and 3/4" sizes.



RS Repair Sleeve

In 3/8", 1/2", 5/8", and 3/4" sizes.



GT Cable Guide Tube

Adds safety when you can't get machine close to drain opening. 5 ft. extension attaches to cable guide tube.



GTE Guide Tube Extension

30" long and 1" in diameter. Easily attaches to 5 ft. extensions, made of rigid conduit with flexible end.

Cables

Flexicore® Cable



Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870



General Flexicore® Cable with Male and Female Connector



"SP" Connector

SP cables are available in 5/8" and 3/4" diameter.

Sectional Cables

Sections for Model 88, Hot-Rodder and Rodrunner come in the all purpose Flexichain which has a chain center, a stiffer Proflex which has a spring center, and a hollow style. Proflex is also available with a heavier duty 5/8" spring center.

Choose from three coupling styles. They snap together in a second and are taken apart quickly with a spanner wrench or uncoupling key. With the more recently developed "G" connector, no torque is put on the locking pin when running in reverse, making it a durable coupling.



Flexichain® Section



Proflex® Cable



"G" Connector Pat. No. 3094011



"L" Connector



15R10-P Proflex® Cable