


Cutters



AH
Arrow Head Starting Drill For 5/16", 3/8", and 1/2" cable.



1-1/4" SCB
1-1/4" Side Cutter Blades For cutting and scraping. For 5/16" and 3/8" cable.



1/4" and 5/16" Down Head
Lead cable down the stack – not up. For 1/4" and 5/16" cable.



1/4" and 5/16" Double Down Head
For especially difficult bends. For 1/4" and 5/16" cable.



FAH
Flexible Arrow Head For sharp turns in small lines. For 5/16" and 3/8" cable.



DHGB
Down Head Boring Gimlet Goes down waste, not up the stack. For 5/16" and 3/8" cable.



BG
Boring Gimlet For removing loose objects. For 5/16" and 3/8" cable.



DHF
Down Head Fitting Can be used with all standard Handylectric cutters. For 5/16" and 3/8" cable.



LE-1 Small Flexible Leader
Attach to 1/2" wire rope center snakes to go through "P" traps and other close bends. For 3/8" and 1/2" cable.



RTR-1
Small Corkscrew Retrieving Tool For removing loose objects. For 3/8" and 1/2" cable.



1-1/2 UC
1-1/2" U-Cutter For cutting and scraping. For 3/8" and 1/2" cable.



2UC
2" U-Cutter For cutting and scraping. For 1/2", 5/8", and 3/4" cable.

SCB
Side Cutter Blades (Two Piece Set) For cutting and scraping. Furnished in 2", 3", and 4" sizes. For 1/2", 5/8", and 3/4" cable.



RSB
Rotary Saw Blades (Two Piece Set) For cutting and scraping. Furnished in 3" and 4" sizes. For 1/2", 5/8", and 3/4" cable.

For 5/8" and 3/4" Cable Machines



SHD
Spear Head Starting Drill



RTR-2
Corkscrew Retrieving Tool For removing loose objects.



HDSC
Heavy Duty Side Cutters In 3" and 4" sizes.



UC
2", 3", and 4" U-Cutters For cutting and scraping.



SCB
Side Cutter Blades For cutting and scraping. Furnished in 3" and 4" sizes.




RP-2
Root Ripper Heavy spring screws into root mass, while front hook tears into stoppage. Passes through 4" "P" Traps.



RSB
Rotary Saw Blades For roots and other stoppages. Furnished in 3" and 4" sizes.



3-6HDEC
Heavy Duty 3" to 6" Expansion Cutter Can pass through 3" pipe to reach and clean 6" pipe. Can be put through 4" "P" traps.



HDB
Heavy Duty Saw Blades For roots and other stoppages. Furnished in 3", 4", and 6" sizes.



FB
Five Blade Fan Type Digger For digging and removing silt, sand, etc.



4-6 SAC
Self Adjusting 4" to 6" Side Cutter Blades Can pass through 4" pipe to reach and clean 6" pipe.



LE-2 - Large Flexible Leader
Used with both 3/4" or 5/8" wire rope center cables to go through "P" traps and other tight bends.



LE-3 - Large Flexible Leader
Used with both 3/4" or 5/8" wire rope center cables to go through "P" traps and other tight bends.



Cutter Set for 7.5R7, 7.5R8 – 5/8" Sectional Cables



R-AH
Arrow Head



R-BG
Boring Gimlet
For removing loose objects.



R-1-1/2 UC
1-1/2" U-Cutter
For cutting and scraping.



R-RTR-1
Corkscrew Retrieving Tool.
For removing loose objects.

Cutter Set for 15R10 – 7/8" Cables



R-SHD-10
Spear Head



R-HA-10
Hook Auger
For breaking up stoppage and retrieving.



R-2UC-10
2" U-Cutter
For cutting and scraping.



R-3UC-10
3" U-Cutter
For cutting and scraping.



R-RTR-10
Corkscrew Retrieving Tool
For removing loose objects.

Rodrunner/Model 88 Standard Cutter Set

(Note all cutters illustrated with "G" connector. If ordering with "L" connector, drop "G" prefix and substitute "L". For example: L-SHD.)



G-SHD
Spear Head



G-2UC
2" U-Cutter



G-3HDSC
3" Heavy Duty
Side Cutter



G-4RSB
4" Rotary
Saw Blade



G-3HDB
3" Heavy
Duty Saw Blade



G-RTR2
Retrieving Tool



CW
Coupling Wrench
(Fits both "G" and "L" connectors.)



G-HA
Hook Auger

Rodrunner/Model 88 Optional Equipment

G-SC
Spade Cutter
Wide blade with sharp edge.



G-CA
Cutter Adapter
Converts all cutters on
page 34-35 for use with
"G" connectors.



G-BA
Bulb Auger
Coiled from heavy gauge
oil-tempered wire for use in
4" plastic pipe.



WCC
Wheeled
Cable
Carrier
Holds five
10-ft. sections.



G-FSH
Flex-Spear
Good in 4" "P" traps.



G-CL
Cutter Leader
Adds flexibility to front of Proflex cables.



CF
Cable Feeding Tool
(Standard with Model 88)
Helps work cable around tight bends.



CC
Cable Carrier
Holds five 10-ft. sections.



Accessories



Snake Oil™

Protects your cables better than common lubricants. Its special rust inhibitor cuts through moisture and replaces it with a rust-resistant coating. In addition, Snake-Oil gives your equipment a fresh, clean smell.



Catalog Number	Description
SOQ	1 Quart Snake-Oil
SOQ-12	12 Quarts Snake-Oil
SOG	1 Gallon Snake-Oil
SOG-4	4 Gallons Snake-Oil




SIG
Splash/Impact Goggles
 Can be worn over glasses.



SG Cable Starter Guide

Guides cable away from trap. Position in pipe by hooking wire into hole in Guide.



Guide Tube Extension

30" long and 1" in diameter. Easily attaches to 5 ft. extensions, made of rigid conduit with flexible end.



GT Cable Guide Tube

Adds safety when you can't get machine close to drain opening. 5 ft. extension attaches to cable guide tube.

QF "Quick Fix" Repair Coupler

Just screw on tightly and it won't come off. For 1/2", 5/8", and 3/4" sizes.



FC Butt-Weld Connector

Passes through automatic feeds. No need to adjust feed. For 5/8", and 3/4" sizes.



FC-O Cup Type Connector

Sheath fits over cable for easier repairs. For 5/16", 3/8", 1/2", 5/8" and 3/4" sizes.



RS Repair Sleeve

In 3/8", 1/2", 5/8", and 3/4" sizes.



Cables

Flexicore® Cable



Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870



General Flexicore® Cable with Male and Female Connector



"SP" Connector

SP cables are available in 5/8" and 3/4" diameter.

Sectional Cables

Sections for Model 88, Hot-Rodder and Rodrunner come in the all purpose Flexichain which has a chain center, a stiffer Proflex which has a spring center, and a hollow style. Proflex is also available with a heavier duty 5/8" spring center.

Choose from three coupling styles. They snap together in a second and are taken apart quickly with a spanner wrench or uncoupling key. With the more recently developed "G" connector, no torque is put on the locking pin when running in reverse, making it a durable coupling.



Flexichain® Section



Proflex® Cable



"G" Connector Pat. No. 3094011



"L" Connector



15R10-P Proflex® Cable

