

Speedrooter 91™

Easier Handling – Same Toughness



The Speedrooter 91 has root cutting power plus the ability to do small drain work. For smaller lines, you switch to a drum that holds 1/2" cable, a job that takes less than a minute. Just loosen three knobs, swing the motor to the side, and lift off the drum.

The power cable feed drives 3/4", 5/8", and 1/2" cables and has the pulling power to get your cable out of the line even on long, tough jobs. To adjust for 3/4" or 5/8" cables, you simply turn the knob on top of the feed. The screwdriver stays in the tool box.

Getting to and from the job is easier because the Speedrooter 91 has big ten-inch wheels, V-belt stair climbers to get up and down stairs easier, and a loading wheel mounted on the handle to help you lift the machine into a truck.

This lean but tough machine can really take a beating, with extra bracing at key stress points. The drum is supported front and back for longer bearing wear and smoother operation. The large drum has a see-through inner cage, so that the operator quickly can tell how much cable is left in the drum.

Standard equipment also includes a Ground Fault Circuit Interrupter and an "Off" position on the reverse switch, so the machine won't start if the pedal is pressed accidentally.





Portability, Convenience, and Safety

Equipped with ten-inch wheels, stair climbers, tool box, and Ground Fault Circuit Interrupter.



Easy Drum Removal

Just loosen three knobs, swing the motor to the side, and lift off the drum.



Stair Climbers and Truck Loaded Wheel

V-Belt and stair climbers let you take the Speedroooter up a flight of stairs yourself. One person can easily load the machine onto the truck.



Small Drum

Holds up to 100 ft. of 1/2" Flexicore cable.

Specifications:

Weight:

115 lbs. (52 kg) without cable.

Dimensions:

26" deep; 22" wide; 41" high, (66 cm x 56 cm x 104 cm).

Interchangeable Drums:

A smaller V-belt is required to drive smaller drum and is standard equipment with PS91-A.

Large Drum:

Equipped with inner drum cage and distributor tube; holds 100 ft. x 3/4" or 5/8" cable.

Small Drum:

Equipped with inner drum and distributor tube; holds 100 ft. of 1/2" cable.

Drum Removal:

Loosen three knobs, swing motor to the side and lift drum off frame.

Motor:

1/2 hp with capacitor start, overload protection, and forward-off-reverse switch. 20 ft. power cord and Ground Fault Circuit Interrupter.

Load Speed:

170 rpm.

Wheels:

10" semi-pneumatic with roller bearings. Brake locks wheels during operation.

Foot Switch:

Pneumatic, with no electrical contact between pedal and motor.

Power Cable Feed:

Drives or retracts cable with variable speed at up to 20 ft./min. without having to reverse motor rotation.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

Cutters:

See Parts and Accessories on page 34.

Cables:

3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 3" to 4" lines. (Not for roots.)

Truck Loading Wheel:

Enables one person to lift machine onto bed of truck.

Tool Box:

Attached to rear of machine.

Stair Climbers:

V-belts running on nylon rollers.