

Root 66™

Uses Sectional Cables for 1-1/4" Thru 4"



Optional Drum
Hold 5/16" and 3/8" cables
for small drain work.



The Root 66 is a real advance in sectional cable machine design. No mid-range machine has its versatility and power.

Look at its versatility. You can drive 5/8" cables for lines up to 3" and 7/8" cables for 4" lines – and you can switch from one to the other in seconds, without touching the jaws, without an adapter, without tools. And for sink drain work, slip on a drum that holds smaller cables.

To operate, just feed a cable into the line and slide the back end into the machine. The excess cable goes into a guide tube. Turn on the sealed motor, press down on the handle, and the Root 66 starts spinning the cable at 400 rpm.

The cable stops rotating as soon as you lift the handle, so there's no additional torque buildup. When using a drum for small drain work, the drum stops turning when you lift the handle to the neutral position.

The Root 66 has a wide four point base for greater stability. Its interlocking tubular construction also gives it excellent durability. To protect the gears from dirt and for easier cleaning, the machine has two internal plastic shields. A Ground Fault Circuit Interrupter is standard equipment.





Optional Dolly

A dolly that clamps onto the Root 66 in seconds.



Root 66 Accessories

Includes cable carriers, drums for small drain work, a rear guide hose, and a tool box. (Standard on 7/8" units.)



Universal Jaws

Jaws handle both 7/8" cables (shown) or 5/8" cables. No adapter required.

"R" Type Sectional Cables for the Root 66



Specifications:

Weight:

42 lbs. (19 kg).

Dimensions:

16" deep; 14" wide; 17" high (40 cm x 35 cm x 43 cm).

Motor:

Sealed 1/2 hp with forward-off-reverse switch, ten-foot power cord and Ground Fault Circuit Interrupter.

Drums:

Small drum holds 25 ft. x 5/16" cable for 1-1/2" to 2" lines.
Large drum holds 35 ft. x 3/8" cable for 2 to 3" lines.

Drip Guards:

Two shields to protect bearings and motor from dirt and moisture.

Clutch:

Pull down two position handle to spin cables at 400 RPM.
Lift to stop. Brake stops spinning drums instantly.

Cables:

"T" slot couplings slide together to lock and uncouple with a pin key. 7.5R8 - 7-1/2 ft. x 5/8" (2.3 m x 15.6 mm) for 1-1/4" through 3" (31 mm - 75 mm) lines up to 125 ft long;
15R10 or 15R10P with Proflex inner core -
15 ft. x 7/8" (4.6 m x 22 mm) for 2" - 4" (50 mm - 100 mm) lines up to 150 ft. long.

Cutter Set:

Cutter Set for 7/8" cables includes Spear Head, 2" U-Cutter, 3" U-Cutter, Hook Auger, and Retrieving Tool.

Cutter Set for 5/8" cables includes Arrow Head, Boring Gimlet, 1-1/2" U-Cutter, and Retrieving Tool.

Jaws:

Drive both 5/8" and 7/8" cables without adjustment; also grip containers for smaller diameter cables. Keyed for longer life and less slippage.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.