

J-3055 Gas Jet

*The most flow
you can get
without a
holding
tank.*



J-3055 Specifications:

Pump:

Triplex w/Vibra-pulse®

Pressure:

3000 psi

Flow:

5.5 gpm

Engine:

16 hp w/Low oil shut off, electric start, and gear reducer

Hose Reel:

Removable, brass swivel, drag brake and reel lock
300 ft. x 3/8" hose capacity

Weight:

280 lbs. (127 kg)

Dimensions:

35" L x 29" W x 47" H
(89 cm x 74 cm x 119 cm)

The J-3055 has the power to clear your most stubborn grease stoppages. Its 3000 psi, 5.5 gallon per minute triplex pump has the thrust to pull the hose down long runs, the pressure to cut through grease stoppages, and the flow to flush them away. In fact, the J-3055 has the highest flow rate available without requiring a holding tank. It's driven by a 16 hp Briggs and Stratton Vanguard engine with electric start. The pump features Vibra-pulse® on demand, for getting the hose around tight bends.

Standard safety features include a thermal relief valve to protect the pump from heat damage, along with a back flow check valve and inlet filter. A removable 300 ft. capacity hose reel with drag brake, reel lock, and brass swivel is mounted on a heavy duty frame with four pneumatic tires. A wheel brake engages with the touch of your foot to keep the machine solidly positioned on the job or on your truck. Complete with tool box, chemical injector, and spray wand with trigger.