

# J-3080 Gas Jet

*Get high water flow without a trailer.*

The J-3080 gives you the increased cleaning power of 8 gallons of flow per minute without risking pump damage if your water supply can't match the pump demand. A 12 gallon buffer tank mounted on the frame gives you the safety margin you need when using a high flow water jet to clear larger and more difficult lines. The tank extends the operating time as well. A 20 hp Honda engine with electric start drives a 3000 psi, 8 gpm pump through a 2 to 1 gear reducer. The pump features Vibra-pulse® on demand, to help propel the hose on long runs and around tight bends.

Standard safety features include a thermal relief valve to protect the pump from heat damage, along with a back flow check valve and inlet filter. The unit is mounted on a heavy duty frame with four 13" pneumatic tires. A wheel brake keeps the machine solidly positioned on the job. Complete with tool box, chemical injector, and spray wand with trigger.

## J-3080 Specifications:

**Pump:**

Triplex w/Vibra-pulse®

**Pressure:**

3000 psi

**Flow:**

8 gpm

**Engine:**

20 hp Honda  
w/Low oil shut off,  
electric start, and  
gear reducer

**Tank Capacity:**

12 gallons

**Weight:**

295 lbs. (134 kg)

**Dimensions:**

37" L x 30-1/2" W x 42-1/2" H  
(94 cm x 77.5 cm x 108 cm)



## CR-300 Cart-Reel™

The optional Cart-Reel™ is a must for professionals. It lets you use the power of a gas jet in buildings and confined spaces where exhaust fumes could be hazardous, while the gas jet stays outside. The Cart-Reel comes with pneumatic tires, a 300 ft. capacity hose reel, reel brake, gauge, and a shut-off valve.

