

# Speedrooter 91™

The Speedrooter has a reputation for being a machine that really can take a beating. Its frame is braced at key stress points, the drum is supported front and back for longer bearing wear, and General's unique Flexicore® wire rope center cables are so tough they carry a one year limited warranty.

To make the new Speedrooter 91 even more user friendly, we've redesigned the frame to make it easier for you to load onto a truck. As it's being loaded, the machine slides smoothly from the loading wheel to the handle to the stair climbers and finally to the wheels.



We've also given the Speedrooter 91 an adjustable height handle. It can be three inches longer or more compact, depending upon your preference. And the machine has a swivel motor mount that swings to the side for more clearance when switching drums.

For those smaller lines, you can switch to a small drum that holds 100 feet of 1/2" cable, a job that takes less than a minute. Just loosen three knobs, swing the motor out of the way, and lift off the drum.

The power cable feed drives 3/4", 5/8", and 1/2" cables and has the pulling power to get your cables out of the line, even on long, tough jobs. To adjust 3/4" or 5/8" cables, you simply turn the knob on top of the feed. The screwdriver stays in the tool box.

The large drum has a see-through inner cage, so you can quickly tell how much cable is left in the drum.



One person easily loads the Speedrooter 91 onto a truck. The swept-back handle and loading wheel give you the leverage.

**The toughest tools down the line.™**

**General** / **General Wire Spring Co.**  
**PIPE CLEANERS**

1101 Thompson Avenue • McKees Rocks, PA 15136 USA  
800-245-6200 or 412-771-6300 • Fax: 412-771-2771  
www.drainbrain.com • e-mail: info@drainbrain.com

# Speedrooter 91™ Units

## Complete and Ready to Operate

**PS91-A** with one 100 ft. x 3/4" (30 m x 190 mm) cable in large drum; one 10 ft. x 1/2" (30 m x 12.7 mm) cable in small drum; and COSC combination cutter set.

**PS91-B** with one 75 ft. x 3/4" (22.5 m x 19 mm) cable and SRCS cutter set.

**PS91-C** with one 100 ft. x 3/4" (30 m x 19 mm) cable and SRCS cutter set.

**PS91-E** with one 100 ft. x 5/8" (30 m x 15.80 mm) cable and SRCS cutter set.

Just pull the motor latch pin, and the motor drops out of the way for easy drum removal.

V-belt stair climbers like the ones used to move heavy furniture and appliances. Lets you take the Speedrooter 91 up a flight of stairs yourself.



Equipped with ten inch wheels, stair climbers, tool box, and ground fault circuit interrupter.

Small drum holds up to 100 ft. of 1/2" Flexicore cable

### FLEXICORE® CABLE



#### Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 42-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870

## SPECIFICATIONS:

### Weight:

115 lbs. (52 kg) without cable

### Dimensions:

26" deep; 22" wide; 41" high.  
(66 cm x 56 cm x 104 cm)

### Drums:

Large drum holds 100 ft. x 3/4" cable.  
(30 m x 19 mm). Optional small drum holds 100 ft. x 1/2" cable (30 m x 12.7 mm).

### Drum Removal:

Loosen three knobs, tilt motor back, and lift off.

### Motor:

1/2 hp with capacitor start, forward-off-reverse switch.  
20 ft. power cord and ground fault circuit interrupter.

### Foot Switch:

Pneumatic, with no electrical contact between pedal and motor.

### Power Cable Feed:

Drives and retracts cable at variable speed without having to reverse motor rotation.

### Wheels:

10" semi-pneumatic with roller bearings.

### Stair Climbers:

Heavy duty V-belts running on nylon rollers.

### Wheel Brake:

Keeps machine in place after it has been positioned by drain opening.

### Truck Loading Wheel:

Enables one person to lift machine onto bed of truck.

### Tool Box:

Attached to rear of machine.

### Leather Gloves:

For hand protection when guiding cable.

### Cables:

Left-wound Flexicore wire rope center 3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 2" to 3" lines.

### Cutter Set:

33" Flexible Leader, Spear Head, 2" U-Cutter, 3" Side Cutter Blades, 4" Side Cutter Blades, 3" Heavy Duty Saw Blade, 4" Rotary Saw Blades, and Large Retrieving Tool.

### Additional Cutter Set:

13" Flexible Leader, Arrow Head, 1-1/2" U Cutter, 2" Side Cutter Blades, Small Retrieving Tool.

**The toughest tools down the line.™**

**General** / **General Wire Spring Co.**  
**PIPE CLEANERS**  
1101 Thompson Avenue • McKees Rocks, PA 15136 USA  
800-245-6200 or 412-771-6300 • Fax: 412-771-2771  
www.drainbrain.com • e-mail: info@drainbrain.com