

I-95™

It's three machines in one.

Here's a sectional cable machine that drives 7/8" and 5/8" sections – or even 5/16" cables for small drain work. You can switch from 7/8" to 5/8" and back by repositioning the chuck cone. *No adapter required.* Attach a small drum to the back of the machine to drive smaller cables.

The I-95 gives you more than versatility. It gives you power and convenience. The motor is a 1/3 hp capacitor type, so it delivers plenty of torque to the cables. Yet, as soon as you lift the drive handle, the cable stops rotating, so there's no additional torque build up.

You also use the drive handle to carry the machine. And when the I-95 is in position on the job, its four point base gives it rock-solid stability. A cutter holder is attached to the back so your cutting heads are always with the machine. A ground fault circuit interrupter is standard equipment.



Clear 4" lines up to 150 feet long with 7/8" x 15' sections...



or clear 1-1/2" – 2" lines with 5/16" x 25' cable ...



or clear 2" – 3" lines up to 125 feet long with 5/8" x 7-1/2' sections.

The toughest tools down the line.™

General / **General Wire Spring Co.**
PIPE CLEANERS

1101 Thompson Avenue • McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300 • Fax: 412-771-2771
www.drainbrain.com • e-mail: info@drainbrain.com

Continued next page

I-95™ Units

I-95-A with six 7-1/2 ft. x 5/8" sections (7.5R8), an SCC small cable carrier and an R-8CS cutter set. Boxed Wt. 74 lbs. (33.5 kg)

I-95-C with five 15 ft. x 7/8" sections (15R10), a CC cable carrier, and R-10CS cutter set and a tool box.
Boxed Wt. 124 lbs. (56 kg)

I-95-D Combines Units A and C.
Boxed Wt. 145 lbs. (66 kg)

I-95-E Same as I-95-D, plus small drum (95-25A) with 25 ft. x 5/16" cable (25HE1-A) installed.
Boxed Wt. 155 lbs. (70 kg)

SPECIFICATIONS:

Weight:
39 lbs. (18 kg)

Dimensions:
14" deep x 12" wide x 23" high.
(35.5 cm x 30.5 cm x 58.4 cm)

Motor:
1/3 hp with forward-off-reverse switch, ten foot power cord, and ground fault circuit interrupter.

Adjustable Chucks:
Has two sets of notches; one for 5/8" cables and one for 7/8" cables. Switch from one diameter to the other in seconds.

Leather Gloves:
Double palm, for hand protection when guiding cable.

Cables:
OT slot couplings slide together to lock and uncouple with a pin key.
7.5R8 - 7-1/2 ft. x 5/8" (2.3m x 15.6 mm) for 1-1/4" through 3" (30 mm \varnothing 75 mm) lines up to 125 ft long;
15R10 or 15R10P with Proflex inner core \varnothing 15 ft. x 7/8" (4.6 m x 22 mm) for 2" \varnothing 4" (50 mm \varnothing 100 mm) lines up to 150 ft. long.



Cutter Sets:
Cutter set for 7/8" cables includes Spear Head, 2" U-Cutter, 3" U-Cutter, Hook Auger and Retrieving Tool.
Cutter set for 5/8" cables includes Arrow Head, Boring Gimlet, 1-1/2" U-Cutter and Retrieving Tool.

Light weight I-95 is easy to carry up a ladder.

15R10-P Proflex Cable

Accessories include cable carriers, drums for small drain work, a rear guide hose, and a tool box (standard on 7/8" cable units.)

Optional 7/8" sectional cable (15R10-P) with Proflex inner core gives cable more strength for cutting through difficult stoppages.



The toughest tools down the line.™
General / **General Wire Spring Co.**
PIPE CLEANERS
1101 Thompson Avenue, McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300 Fax: 412-771-2771
www.drainbrain.com e-mail: info@drainbrain.com