

Root 66™

Ready for all your inside and rooftop jobs.

The Root 66 is a real advance in sectional cable machine design. No mid-range machine has its versatility and power.



Look at its versatility. You can drive 5/8" cables for lines up to 3" and 7/8" cables for 4" lines – and you can switch from one to the other in seconds, without touching the jaws, without an adapter, without tools. For sink drain work, slip on a drum that holds smaller cables.

To operate, just feed a cable into the line and slide the back end into the machine. The excess cable goes into a guide tube. Turn on the sealed motor, press down on the handle, and the Root 66 starts spinning the cable at 400 rpm.

The cable stops rotating as soon as you lift the handle, so there's no additional torque buildup. When using a drum for small drain work, the drum stops turning when you lift the handle to the neutral position.

The Root 66 has a wide four point base for greater stability. Its interlocking tubular construction also gives it excellent durability. To protect the gears from dirt and for easier cleaning, the machine has two internal plastic shields.

- Wide four-point base for greater stability.
- Heavy-duty sealed 1/2 hp motor.
- Bearings are protected from dirt and moisture by two gaskets.
- Ground fault circuit interrupter for electrical safety.
- Oversize keyed jaws for longer life and less slippage. The same jaws drive both 5/8" and 7/8" cables.
- Optional dolly for easy transport over long distances.



Optional drums hold 5/16" and 3/8" cables for small drum work.

Universal jaws that handle both 7/8" cables (shown) or 5/8" cables. No adapter required.

The toughest tools down the line.™

General / **General Wire Spring Co.**
PIPE CLEANERS | 1101 Thompson Avenue • McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300 • Fax: 412-771-2771
www.drainbrain.com • e-mail: info@drainbrain.com

Continued next page

Root 66 Units

Complete and Ready to Operate
(Includes rear guide tube)

RT-66-A with six 7.5R8 sections, an SCC cable carrier, and a R-8CS cutter set. Boxed wt. 72 lbs. (32 kg)

RT-66-C with five 15R10 sections, a CC cable carrier, an R-10CS cutter set. Boxed wt. 122 lbs. (55 kg)

RT-66-D Combines units A and C. Boxed wt. 143 lbs. (65 kg)

RT-66-E Same as RT-66-D, plus drum with 25' x 5/16" cable (25HE1-A) installed. 153 lbs (69 kg)

Accessories include cable carriers, drums for small drain work, a rear guide tube, and a tool box (standard on 7/8" cable units.)



An optional dolly that clamps onto the Root 66 in seconds.

15R10-P Proflex® Cable



Optional 7/8" sectional cable (15R10-P) with Proflex inner core gives cable more strength for cutting through difficult stoppages.

SPECIFICATIONS:

Weight:

42 lbs. (19 kg)

Dimensions:

16" deep; 14" wide; 17" high.
(40 cm x 35 cm x 43 cm)

Motor:

Sealed 1/2 hp with forward – off – reverse switch, ten foot power cord and ground fault circuit interrupter.

Drums:

Small drum holds 25 ft. x 5/16" cable for 1-1/2" to 2" lines.
Large drum holds 35 ft. x 3/8" cable for 2 to 3" lines.

Drip Guards:

Two shields to protect bearings and motor from dirt and moisture.

Clutch:

Pull down two position handle to spin cables at 400 RPM. Lift to stop. Brake stops spinning drums instantly.

Cables:

7 1/2 ft. x 5/8" (Cat #7.5R8) for 1-1/4 to 3" lines up to 125 ft.
15 ft. x 7/8" (Cat # 15R10) for 2 to 4" lines up to 150 ft.
"T" slot couplings slide together to lock and uncouple with a pin key.

Cutter Set:

Cutter set for 7/8" cables includes Spear Head, 2" U-Cutter, 3" U-Cutter, Hook Auger and Retrieving Tool.

Cutter set for 5/8" cables includes Arrow Head, Boring Gimlet, 1-1/2" U-Cutter and Retrieving Tool.

Jaws:

Drive both 5/8" and 7/8" cables without adjustment; also grip containers for smaller diameter cables. Keyed for longer life and less slippage.


Leather Gloves:

Double palm, for hand protection when guiding cable.

Cutter Set for 7/8" cables



Cutter Set for 5/8" cables



The toughest tools down the line.™

General / **General Wire Spring Co.**
PIPE CLEANERS

1101 Thompson Avenue • McKees Rocks, PA 15136 USA
800-245-6200 or 412-771-6300 • Fax: 412-771-2771
www.drainbrain.com • e-mail: info@drainbrain.com