

# Metro-Rooter™

## Root Cutting Power at a Great Price

The Metro-Rooter is a tough root cutting machine in a compact, lightweight package, at a price that's easy on tight budgets. With 75 feet of 5/8" cable it handles roots and other difficult obstructions in 3" to 6" lines. This easy to use, one-person operation machine is light enough to take down to the basement or up on the roof.

The Metro-Rooter has many of the features of the bigger capacity root cutting machines, including a variable speed Power Cable Feed that drives and retracts 1/2", 5/8", and 3/4" cable at up to 20 ft. per minute. The heavy-duty powder coated steel drum holds 100 ft. of 1/2" cable for inside lines, 75 ft. of 5/8" cable for roots, or 50 ft. of 3/4" cable for tough jobs. Plus, it features a unique self-aligning Flexitube™ distributor tube to reduce tangling.

The Metro-Rooter's heavy-duty reinforced frame and drum support shaft takes rough handling in the field. The 1/3 hp capacitor motor has plenty of power to drive more than 100 ft. of cable. A passive brake system holds the machine in place on the job or in your truck. The ten-inch wheels and a truck loading wheel make it easier for you to transport the machine to and from the job.



### Specifications:

**Weight:**

92 lbs. (42 kg) without cable.

**Dimensions:**

27" deep x 18-1/2" wide x 46" high  
(26" high with handle folded down)  
68.5 cm deep x 47 cm wide x 117 cm high  
(66 cm with handle folded down)

**Drum Capacity:**

50 ft. x 3/4" (15 m x 19 mm)  
75 ft. x 5/8" (22.5 m x 15.8 mm)  
100 ft. x 1/2" (30 m x 12.7 mm)

**Drum Removal:** Remove one bolt and slide drum off shaft.

**Motor:**

1/3 hp with capacitor start, forward-off-reverse switch, 20 ft. power cord and ground fault circuit interrupter.

**Foot Switch:**

Pneumatic, with no electrical contact between pedal and motor.

**Safety Slip Clutch:** Protects cable and operator.

**Power Cable Feed:**

Drives and retracts cable at variable speed without having to reverse motor rotation.

**Wheels:** 10" semi-pneumatic with roller bearings.

**Wheel brake:**

Passive wheel brake system holds the machine in place on the job and in the truck.

**Truck Loading Wheel:**

Enables one person to lift machine into truck bed.

**Cutter Holder:** Cutter Holder on the frame keeps all the cutters within easy reach.

**Leather Gloves:**

With double-reinforced palm, for hand protection when guiding cable.

**Cables:** Left-wound Flexicore wire rope center. 3/4" for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 3" to 4" lines. (Not for roots.)

**Instructional Video included.**

