

Mini-Router XP™

Extra Portability and Performance


The Mini-Router XP gives you extra portability because 8" semi-pneumatic wheels let you keep the weight on the ground. An easy-grip handle folds down to save space and locks to use as an additional lifting handle.

A roll bar protects the 1/3 hp motor when going up or down stairs. And the power cord and foot pedal can be stowed away on convenient cord wraps.

The XP gives you extra performance and value, enabling you to clear clogged drain lines from 1-1/4" to 4" in diameter with just one machine. The drum easily holds 75 feet of 3/8" or 1/2" cable and features a free floating inner drum with an integral distributor tube to help prevent cable tangling. By switching to the optional J-Drum, you can handle smaller drain lines.

You'll want to equip your XP with a power cable feed too. It makes a lot of tough jobs go much easier. Even with the power cable feed, the drum is a snap to remove, taking less than a minute.

Of course the XP comes with an air foot pedal and Ground Fault Circuit Interrupter for safety, and General's patented Flexicore wire rope center cable for durability.



Power Cable Feed

A variable speed power cable feed makes feeding and retrieving the cable much easier. It quickly adjusts between 3/8" and 1/2" cables without the need for tools or additional parts.

Folding Handle

The handle is tall enough to make it easy to move to the job, yet it can be quickly folded to take less room in your truck.



Specifications:

Weight:

67 lbs. (30 kg) with power feed and without cable.

Dimensions:

24" deep x 18" wide x 38" high with handle folded down.
(61 cm x 46 cm x 96 cm).

Drum:

Equipped with inner drum and distributor tube to prevent cable tangling under load. Quickly removable from frame.

Wheels:

8" semi-pneumatic tires with oilite bronze bushings.

Folding Handle: Reduces storage space.

Cutter Set: See page 14.

Motor:

1/3 hp with forward-off-reverse switch, spring-loaded mounting for proper belt tension. Load speed 165 rpm.

Safety Slip Clutch: Protects cable and operator.

Belt Guard:

High impact plastic secured with a tension knob.

Power Cable Feed:

Drives 1/2" and 3/8" cables.

Foot Pedal:

Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord: 10 ft. 3-wire. In-line Ground Fault Circuit Interrupter.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

J-Drum: See Page 4.

Instructional Video Included.

