

Connectors



QF – “Quick- Fix”

Just screw on tightly and it won't come off. For 3/4", 5/8", and 1/2" cables.



RS – Repair Sleeve

In 3/8", 1/2", 5/8", and 3/4" sizes. (weld on).



FC-O – Female Connectors

3/8", 1/2", 5/8", and 3/4" (weld on).



MC-O – Male Connectors

3/8", 1/2", 5/8", and 3/4" (weld on).



Snake Oil

It protects your cables better than common lubricants. Its special rust inhibitor cuts through moisture and replaces it with a rust-resistant coating. In addition, Snake-Oil gives your equipment a fresh, clean smell. Available in quarts and gallons.



Screw-in Connectors and Splicers

5/8" and 3/4" (Wire rope center must be removed with 1/8" drill bit rotating at very slow speed.)

Cables

Sectional Cables

Quick coupling “Cable Saver” sectional cables for the Model 88 and Rodrunner.

Choose from two coupling styles. Both snap together in a second and are taken apart quickly with a spanner wrench or even a screwdriver.

With the more recently developed “G” connector, no torque is put on the locking pin when running in reverse, making it a very durable coupling.



Flexichain Sections

1-1/4" outer spring wrapped around a center gives unmatched flexibility to get through tight traps and difficult bends, while providing maximum protection against losing broken cables in a line. Outer spring is right-hand wound for faster feeding. Available in 8 and 10 ft. lengths with “G” or “L” connectors.



Proflex Sections

Combination of 1-1/4" outer spring with 1/2" Proflex inner spring to better handle motor torque and have better “push” when working through tough stoppages. Outer spring is right-hand wound and inner spring is left-hand wound for greater strength and durability. Available in 4, 8 or 10 foot sections with “G” or “L” connectors.



Heavy Duty Proflex Sections

Same 1-1/4" outer spring as the Proflex but with a 5/8" heavy duty inner spring to provide more torque for difficult stoppages and longer runs. Available in 4, 8 or 10 foot sections with “G” or “L” connectors.



6 ft. x 7/8" Proflex Sections (Cat # 6L78)

For 2" to 4" drain lines up to 100 ft. long. It combines a 6 ft. x 7/8" outer cable with 7/16" Proflex inner spring giving you the flexibility to get through small lines with the strength to resist kinking. For use with the Model 88 using the 78L-CDC Drive Coupling or the 78L-AD Adapter. Available with “L” connector.



Flexicore® Cable



Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated.

Has unequalled strength and the right amount of flexibility.

So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870