

Mini-Router™

Clears Lines from Rooftop to Basement



The Mini-Router clears lines from rooftop to basement, including kitchen, bath and laundry. With 50 ft. of 1/2" cable, it weighs just 60 lbs.

This inexpensive, easy-to-use machine has lots of time saving features. For instance, you can remove the zinc-plated cage in seconds for more portability or to switch to a different cable diameter – with no mess or lost time. Safety features include an air foot switch, ground fault circuit interrupter, and a safety slip clutch. An integral inner drum and distributor tube help prevent cable tangling under load.



For small drain work, get a Mini-Router J-Drum.



Dolly snaps on frame for easier portability.



Take the cage off the Mini-Router in seconds.



Flexicore® Cable

Wire Rope Center Construction

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870

Specifications:

Weight: 32 lbs. without cable. (14.5 kg)

Capacity: 75 ft. of 3/8" or 1/2" Flexicore Cable.

Motor: 1/3 hp, thermal overload protection, Forward/Off/Reverse Switch.

Safety Slip Clutch: Protects cable and operator.

Flexicore Cable: Heavy gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated.

Foot Pedal: Uses air pressure, so there's no electrical contact between pedal and motor.

Power Cord: 10 ft., 3-wire; equipped with ground fault circuit interrupter.

Cutter Set: Arrow Head, 1-1/2" U-Cutter, 2" Side Cutters and Boring Gimlet. Others available.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

Instructional Video included.

